Wellock Large Opening Vise



World Famous & High Accuracy & Best Quality & Large Opening

ATW Vise offers the high quality as same as the world famous brands. Improving on industry standards, the vises are ultra-precision in datum, flatness, parallelism and verticality.


- Wellock Semi-spherical segment eliminate deflection and lift.
- Rigid and tensile ductile iron FCD-60 (80,000PSI) vise body. Slide surface flame hardened to HS65° to maintain the accuracy. S50C jaw-plate has been Carburizing heat treated the hardness to HRC54°.
- 4 different clamping positions.
- Bearing system has sealed and special treated to reduce damage for extend the lifetime.
- 8,200lbs high clamping force.

















4 Jaw-plate Positions







	Wellock VISE system												
NO	Inspe	Allowance [mm]											
		Auto Well	JIS. Class										
1	Parallelism	running face to bottom of bed	0.01	0.015									
2	Squareness	between running face and jaw plate	0.01	0.03									
3	Squareness	keyways on bottom of bed to jaw plate	0.015	0.015									
4	Parallelism	keyways on bottom of bed to jaw plate	0.01	0.015									
5	Squareness	both sides to running face	0.015	0.02									
6	Squareness	both sides to fixed jaw plate	0.015	0.03									

^{*}Basic on global market, our company start producing MC serious type of vise on 1986 and we keep our vise dimensions as same since then. There is no fitment or alignment problem between our old and new MC vise.

Wellock Large Opening Vise

ATW-689/810

Workholding

689



ATW-689


- 8.9" large opening.
- Spindle nut does not protrude past the end of body.
- Same distance from keyway to stationary jaw with AT-675.
- Bed height 73.025 ± 0.012 mm $(2.875\pm0.001")$.




ATW-810

- Updated body from AT-80, it provides 10" large opening and steadier vise body.
- Bed height 84.074±0.012mm (3.26±0.001").
- [8] 11,600lbs clamping force.

ATW-689/810 Dimensions





ATW DIMENSIONS															mm/kg				
NO	A	В	C	D	E	0	G	B	0	U	K		M	N	0		U	Weight	
ATW-689	437	222	151	481	111.025	44	90.5	73.025	52	18	17.48 / 18	123	44.5	19	226	23.8	98.4	36.3kg	
ATW-810	555	295	206	615	134.074	60	125.7	84.074	58	24.2	20.65 / 18	157	56	19	265	32	120	68.2kg	



Wellock Vise

ATW-675 ATD-460/570

Workholding



ATD-460/570





675

ATW-675

- a 7.5" opening.
- Bed height 73.025±0.012mm (2.875±0.001").

2 ATW-675, ATD-460/570 Dimensions





ATW/ATD DIMENSIONS															mm/kg					
NO	A	B	C	D	8	Œ	G	0		J	K	0	M	N	0	0	U	Weight		
ATD-460	321	160	102	361	85.65	40	71	57.15	35.1	15	12	102	35	14	153	17.5	63.5	14kg		
ATD-570	368	194	126	415	97	47	85	63.5	40.5	17	16	120	38.1	16	178	20.6	79.4	21kg		
ATW-675	432	235	151	476	111.025	44	108	73.025	52	18	17.48 / 18	123	44.5	19	192	23.8	98.4	36kg		